

Performance F-A130AS



ACCESS 130 AS

2-way component kit

- (DFS®) Dual Fiberglass Structure cone
High resistance (Power, climatic conditions, humidity...)
- Phase plug
Midrange control
- Grilles new design
Profiled

- Adjustable tweeter level
(3 positions : -3 / 0 / +3dBoct)
Soundstage positioning
- Air core inductors
Insensitive to parasite interferences



- ABS basket with 20% of fiberglass
Non magnetic, non resonant
- 25mm (1") voice coil (2 Kapton® layer)
High power handling

- 85mm magnet
High sensitivity

- Aluminum inverted dome tweeter
Accurate treble

CE QUI FAIT LA DIFFÉRENCE

- Cone DFS® (Dual fiberglass Structure)
(climatic and power) high resistance
- Tweeter level adjustment

TECHNICAL CHARACTERISTICS

Woofer: 5" (130mm)
Voice-coil diameter: 1" (25mm)
Voice-coil height: 0^{7/16}" (11mm)
Magnet: 3^{1/3}" (85mm)
Tweeter: Aluminum inverted dome
Adjustable Tweeter level: 3 positions (-3/0/+3dB)

Crossover: 12dB/oct
Max. power: 100 Watts
Nom. power: 50 Watts RMS
Sensitivity (2.83V/1m): 90dB
Frequency response: 65Hz – 20kHz
Accessories: Supplied grilles

Performance F-A165AS



**ACCESS
165 AS**

2-way component kit

- Adjustable tweeter level
(3 positions : -3 / 0 / +3dBoct)
Soundstage positioning
- Air core inductors
Insensitive to parasite interferences

- (DFS®) Dual Fiberglass Structure cone
High resistance (Power, climatic conditions, humidity...)
- Phase plug
Midrange control
- Grilles new design
Profiled



- ABS basket with 20% of fiberglass
Non magnetic, non resonant
- 25mm (1") voice coil (2 Kapton® layer)
High power handling

- 85mm magnet
High sensitivity

- Aluminum inverted dome tweeter
Accurate treble

WHAT MAKES THE DIFFERENCE

- Cone DFS® (Dual fiberglass Structure)
[climatic and power] high resistance
- High sensitivity [Direct headunit using]
- Tweeter level adjustment Extended in low frequencies

TECHNICAL CHARACTERISTICS

Woofer: 6 1/2" (165mm)

Voice-coil diameter: 1" (25mm)

Voice-coil height: 0 7/16" (11mm)

Magnet: 3 1/3" (85mm)

Tweeter: Aluminum inverted dome

Ajustable Tweeter level: 3 positions [-3/0/+3dB]

Crossover: 12dB/oct

Max. power: 120 Watts

Nom. power: 60 Watts RMS

Sensitivity (2.83V/1m): 91.3dB

Frequency response: 60Hz - 20kHz

Accessories: Supplied grilles

Performance F-A165AS3



**ACCESS
165 AS3**

3 way component kit

- (DFS®) Dual Fiberglass Structure cone
High resistance (Power, climatic conditions, humidity...)
- Grilles new design
Profiled

- Butyl surround
Longlife

- Adjustable tweeter level
(3 positions : -3 / 0 / +3dB/oct)
Soundstage positioning
- Air core inductors
Insensitive to parasite interferences



- ABS basket with 20% of fiberglass
Non magnetic, non resonant
- 25mm (1") voice coil (2 Kapton® layer)
High power handling

- 85mm magnet
High sensitivity

- 80mm (3") midrange
Compact, easy to install

- Aluminum inverted dome tweeter
Accurate treble

WHAT MAKES THE DIFFERENCE

- Cone DFS® (Dual fiberglass Structure),
(climatic and power) high resistance
- High sensitivity (Direct headunit using)
- Compact midrange 3^{1/8} (80mm) [easy to install]
- Tweeter level adjustment - Extended in low frequencies
- Power handling

TECHNICAL CHARACTERISTICS

Woofer diameter: 6^{1/2}" (165mm)

Midrange diameter: 3" (80mm)

Voice-coil diameter: 1" (25mm)

Voice-coil height: 0^{9/16}" (15mm)

Magnet: 3^{1/3}" (85mm)

Tweeter: Aluminum inverted dome

Separate crossover: 12dB/Oct

Adjustable Tweeter level: 3 positions [-3

Max. power: 160W

Nom. power: 80W

Sensitivity (2.83V/1m): 90dB

Frequency response: 55Hz – 20kHz

Accessories: Supplied grilles